Baset EVBMN-M110



HDMI Extender over CAT5 with IR, Ethernet & Serial Extending

Specifications

EVBMN-M110		Transmitter Unit	Receiver Unit	
		EVBMN-110L	EVBMN-110R	
Input → Output		HDMI → RJ-45	RJ-45 → HDMI	
LED	Status LED	Dual Color x 1	Dual Color x 1	
	LAN LED	Single Color x 3	Single Color x 3	
Video Resolution (max.)		UHD (3840 x 2160 @ 30Hz)		
Extension Distance		Full HD 1920 x 1080 @ 100M UHD 3840 x 2160 @ 70M		
Ethernet Port		RJ-45 x 3	RJ-45 x 3	
		10/100 Mbps		
Serial Port		DCE, DB9-F	DTE, DB9-M	
		115kbps (max.)		
IR Extension		x 1, IR Transceiver	x 1, IR Receiver	
Power Supply		DC 12V (Phantom Power)		
Enclosure		Metal		
Weight (gram)		410~420		
H x W x D (mm)		140 x 85 x 34		

^{*}Above video resolution and extension distance are based on a single CAT5e/6 24AWG solid cable without cascade. STP cabling is recommended for environments with high EMI or RFI. For the best performance results, using stranded cabling or other thinner cables, and coiling of excess cable lengths should be avoided.

Related Products (without Ethernet & Serial function)

Type	100M	70M	Function
Tx + Rx	EVBM-M110	EVBM-M107	CAT5 HDMI Extender Pair
Tx (Splitter)	EVBM-1104L	EVBM-1074L	CAT5 HDMI Splitter (2-in / 4-out) with Auto-sensing function
Tx (Switch- Splitter)		EVBM-S1474L	CAT5 HDMI Switch-Splitter (4-in / 4-out) with Auto-sensing function

Features

- Send HDMI signal to multimedia display over CAT5e/6 cable of up to 100 meters
- Transmit full uncompressed HD video and audio over cable
- 100BaseT Ethernet Pass-Thru; simultaneously distribute HDMI and Ethernet streaming video from source to display
- Low cost standard CAT5e/6 LAN cable; advanced and inexpensive all-in-one connectivity technology
- HDCP compliant and Blu-ray ready
- Support Deep Color, HD-3D video and HD Audio formats
- Support resolution up to Full HD 1080p / 4Kx2K (3840 x 2160)
- Bi-directional LAN & Serial

Serial Devices

- Support Phantom Power -- single power supply at either one end of two units (Tx & Rx)
- Compact size; easy to set up; simple to install
- Ideal for hospitality (hotels, conference rooms), digital signage (airports, shopping malls), surveillance cameras, whole-home networking and point-to-point consumer applications

Connection Pattern



